



SAFETY DATA SHEET
530VUP UNIVERSAL SOFT PLUS
BODY FILLER

According to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 530VUP UNIVERSAL SOFT PLUS BODY FILLER

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier ETALON is a brand of Alexport Company.
Pontou 26, P.C. 546 28, Thessaloniki, Greece,
Tel: +30 2310 501814, Fax: +30 2310 524 771
info@alexport.gr, www.alexport.gr
www.etalon-refinish.com

1.4. Emergency telephone number 112 or call your local doctor/poison center

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226
Health hazards Acute Tox. 4 - H302 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 STOT RE 1 - H372
Environmental hazards Not Classified

2.2 Label elements

Hazard pictograms



Signalword Danger

Hazard statements H302+H332 Harmful if swallowed or if inhaled.
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H372 Causes damage to organs through prolonged or repeated exposure.

530VUP UNIVERSAL SOFT PLUS BODY FILLER

Precautionary statements	P102 Keep out of reach of children.
	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P233 Keep container tightly closed.
	P240 Ground and bond container and receiving equipment.
	P260 Do not breathe vapour/ spray.
	P264 Wash contaminated skin thoroughly after handling.
	P270 Do not eat, drink or smoke when using this product.
	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
	P301+P312 IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.
	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
	P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P403+P235 Store in a well-ventilated place. Keep cool.	
P501 Dispose of contents/ container in accordance with national regulations.	

Contains UNSATURATED POLYESTER RESIN, BARIUM SULFATE, STYRENE MONOMER

2.3. Other hazards**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

TALC	20-30%
CAS number: 14807-96-6	EC number: 238-877-9
Classification	
Skin Irrit. 2 - H315	
UNSATURATED POLYESTER RESIN	30-40%
CAS number: —	
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H332	
CALCITE	10-15%
CAS number: 1317-65-3	EC number: 215-279-6
Classification	
Skin Irrit. 2 - H315	
BARIUM SULFATE	5-10%
CAS number: 7727-43-7	EC number: 231-784-4
Classification	
Met. Corr. 1 - H290	
Acute Tox. 3 - H301	
Acute Tox. 4 - H332	

530VUP UNIVERSAL SOFT PLUS BODY FILLER**TITANIUM DIOXIDE****1-5%**

CAS number: 13463-67-7

EC number: 236-675-5

Classification

Skin Irrit. 2 - H315

STYRENE MONOMER**1-5%**

CAS number: 100-42-5

EC number: 202-851-5

Classification

Flam. Liq. 3 - H226

Acute Tox. 4 - H332

Skin Irrit. 2 - H315

Eye Irrit. 2 - H319

Repr. 2 - H361d

STOT RE 1 - H372

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

General information	Move affected person to fresh air at once. Get medical attention.
Inhalation	Remove person to fresh air and keep comfortable for breathing.
Ingestion	Rinse mouth. Get medical attention if any discomfort continues.
Eye contact	IF IN EYES: Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

4.2. Most important symptoms and effects, both acute and delayed**4.3. Indication of any immediate medical attention and special treatment needed****SECTION 5: Firefighting measures****5.1. Extinguishing media**

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or waterfog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	In case of fire: Irritating gases or vapours.
-------------------------	---

5.3. Advice for firefighters

Protective actions during firefighting	In case of fire: Evacuate area. No action shall be taken without appropriate training or involving any personal risk.
---	---

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****6.2. Environmental precautions**

Environmental precautions	Avoid release to the environment. Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

530VUP UNIVERSAL SOFT PLUS BODY FILLER

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions For use in industrial installations or professional treatment only. Obtain special instructions before use. Wear protective gloves, eye and face protection. Wear protective clothing. Do not breathe gas, fume, vapours or spray. Provide adequate ventilation. Keep away from heat, sparks and open flame.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep only in the original container in a cool, well-ventilated place.

7.3. Specific end use(s)

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

STYRENE MONOMER

Long-term exposure limit (8-hour TWA): WEL 100 ppm 430 mg/m³

Short-term exposure limit (15-minute): WEL 250 ppm 1080 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.
Odour Characteristic.
Flash point 34°C

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

10.5. Incompatible materials

10.6. Hazardous decomposition products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 694.44

530VUP UNIVERSAL SOFT PLUS BODY FILLER

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

Serious eye damage/irritation

Serious eye damage/irritation Irritation of eyes is assumed.

Respiratory sensitisation

Respiratory sensitisation May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitisation

Skinsensitisation May cause sensitisation or allergic reactions in sensitive individuals.

SECTION 12: Ecological information

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 3269

UN No. (IMDG) 3269

UN No. (ICAO) 3269

UN No. (ADN) 3269

14.2. UN proper shipping name

Proper shipping name (ADR/RID) POLYESTER RESIN KIT

Proper shipping name (IMDG) POLYESTER RESIN KIT

Proper shipping name (ICAO) POLYESTER RESIN KIT

Proper shipping name (ADN) POLYESTER RESIN KIT

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

530VUP UNIVERSAL SOFT PLUS BODY FILLER**Transport labels****14.4. Packing group**

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III
ADN packing group	III

14.5. Environmental hazards**Environmentally hazardous substance/marine pollutant**

No.

14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.2. Chemical safety assessment****SECTION 16: Other information**

Revision date	31/05/2020
SDS number	003
Hazard statements in full	H226 Flammable liquid and vapour. H290 May be corrosive to metals. H301 Toxic if swallowed. H302 Harmful if swallowed. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H361d Suspected of damaging the unborn child if swallowed. H372 Causes damage to organs through prolonged or repeated exposure.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.